





(985) 385-3310

995 Utah Street
Berwick, LA 70342

Model Number:

1

2072 SCF

Specifications

Hull (standard)

- Length Overall (LOA): 20' (not including motor guard)
- Bottom Width: 70"
- Beam: 94"- 96"
- Side Height: 24" or 30"
- Bottom Thickness: 3/16"
- Side Thickness: 3/16"
- Hull Material: 5086 Marine-Grade Aluminum
- Floor & Decking Material: 1/8" Aluminum Diamond Plate
- Transom Height: 20" - 25"

Structural Design (standard)

Longitudinal Structure (Fore-Aft)

- Qty: 4 | 3" x 1-1/8" corrugated bottom runners pressed into hull plating
- Qty: 2 | 3" x 1-1/8" corrugated side runners pressed into side plating
- Qty: 2 | 3" x 2" x 3/16" aluminum angle rails (inside gunnel)
- Qty: 2 | 2" Schedule 40 aluminum half pipe (outside gunnel)

Transverse Structure (Port-Starboard)

- Collision Bulkhead: 3/16", sealed, fully welded, pressure tested
- Floor Supports: 2" x 2" square tubing on 16" centers
- Secondary Bracing: 1" x 1" angle tacked beneath flooring, between each rib section
- Transom Reinforcement: (2) 4" x 1-1/2" channels across inside of transom with vertical gussets

Floor Plan & Layout (standard)

- Front Deck: 5' aluminum tread plate
- Front Storage: Flush-mounted hinged hatch with dry storage
- Console: Side console with integrated shelf
- Seating: Full-width bench seat
- Seat Storage: Top-mounted hinged lid with dry storage
- Splash Well: Full-width splash well
- Drainage: (2) overboard drains—port and starboard

Transom & Motor Protection (standard)

- Transom Brackets: Corner gussets, anode mount, transducer mount
- Motor Guard: 2" aluminum pipe motor guard
- Guard Bracing: 1-1/2" gusset pipes
- Motor Clearance: Designed to allow full trim of outboard motor

Lifting & Handling (standard)

- Lifting Eyes/Cleats: (4) combination lifting eyes and cleats
- Locations: Port and starboard — bow and stern

Standard Features

Steering & Control

- Steering System: Single-cable manual steering
- Steering Wheel: Included

Lighting & Visibility

- Navigation Lights: Front flush-mounted lights
- All-Around Light: White 360-degree light

Bilge & Drainage

- Bilge Pump: 1,100 GPH automatic bilge pump
- Control: Manual override switch on dash

Fuel System

- Fuel Tank: 12-gallon plastic fuel tank
- Tank Location: Port side mounted
- Fuel System: Fittings, valves, hoses, and fuel-water separator

Electrical & Power

- Power Outlet: 12V USB socket
- Battery: Marine cranking battery
- Battery Installation: Battery case and hold-down strap
- Wiring Protection: All wiring encased in plastic split loom

Corrosion Protection & Hardware

- Anode: Installed ion transom
- Fasteners: Stainless steel fasteners throughout

Fit, Finish & Protection

- Dry Storage Seals: Gaskets on front dry box
- Edge Protection: Trim gaskets on all raw edges



(985) 385-3310
995 Utah Street
Berwick, LA 70342

Model Number:

2

2072 SCF

Options & Upgrades

Commercial Work Package

Push Knees

- Type: Heavy-duty D-Rubber
- Size: 3"
- Location: Bow—port and starboard
- Purpose: Docking, pushing, and workboat contact protection

Side Rubber Rails

- Type: Heavy-duty D-rubber
- Size: 3"
- Coverage: Full outside gunnel—bow to stern
- Purpose: Hull protection during docking and commercial use

6" Wide Rails (catwalk)

- Rail Width: 6"
- Construction: 2" x 3/8" interior flat bar
- Reinforcement: Heavy-duty gusset plates to side wall
- Purpose: Walkable catwalk providing secure footing for crew movement

Upgrades

Fuel Tank Options

- Rear Aluminum Fuel Tank: Replaces standard plastic tank
- Front Step-Style Fuel Tank: Aluminum tank located behind front deck

Flotation & Safety

- Saddle Flotation Pods: Improves flotation and stern lift; eliminates motor guard
- Level Flotation: Internal foam flotation installed from bow to stern

Windshield

- Low-Profile Windshield: 1/4" Plexiglass with integrated 1" Schedule 40 aluminum grab rail

Steering

- Hydraulic Steering System: Recommend for 90-115 HP

Lighting

- Bow-Mounted LED Light Bar: 10" LED light bar mounted in an integrated bow light pocket

Electrical

- 4-Gang Switch Panel: Blue Sea Systems with Perko on/off switch
- 6-Gang Switch Panel: Blue Sea Systems with Perko on/off switch

Communications

- VHF Radio Package: Standard Horizon VHF with 3' antenna

Sound System

- System options to be discussed with your sales rep.

Electronics (GPS/Sonar)

- GPS/Sonar Combo: Garmin 5", 6", or 7" display
- Transducer: External transducer
- Console Integration: Flush-mounted GPS in console

Horn

- Console-Mounted Horn: Flush-mounted into the console

Seating & Comfort

- Driver Seat: Folding seat with removable pedestal
- Passenger Seat: Folding seat with removable pedestal
- Bench Seat Cushion: 2" foam with marine vinyl cover (medium gray)

Paint

- Color options to be discussed with sales rep

Decking

- EVA Foam Decking
- Spray Liner

Power Packages (motors)

Brands

- Honda
- Mercury
- Suzuki

Horsepower

- 75 HP
- 80 HP
- 90 HP
- 100 HP
- 115 HP

Trailer

Galvanized Trailer Package

- Manufacturer / Model: McClain 1920-14 SR
- Type: Single-axle galvanized
- Capacity: 3,000 lbs.
- Tires: 14"
- Side Guides: Heavy-duty
- Bunks: (4) plastic-covered drive-on boards
- Lighting: LED
- Spare: Spare tire with carrier
- Setup: Adjusted and fitted for selected boat